

**Home**Electric

## INSTRUCTION MANUAL air cooler



HACT-2601

Please read the instructions first before using the machine Keep this manual for future reference

TIMER:

Press this button to set the turn-off time for the unit.

The turn-off time can be set in an hour increments from 1 to 8 hours, there are 4 indicators 1H, 2H, 3H and 8H.

MODE:
There are three selectable modes, the corresponding indicator turns on.
Normal mode: The fan operates in the constant speed set using the SPEED button.
Natural mode: The unit simulates a natural breaze.
Sleep mode: The unit simulates agentile breeze suitable for night-time use

SWING:
Press this button to start or stop louvres oscillation from left to right, the corresponding indicator turns on.

COOL:
Press this button for a cool breeze when water is added to the water tank, the corresponding indicator turns on press again to turn off the cool breeze.

1.open battery cover
2.remove and replace the new one .pls note battery positive and negative
3.reset the battery cover




### Functional characteristics

Functional characteristics in increase air humility, wouth beauty; winter air temperature is low, the skin water evaporates too quickly, lips and skin easily become rough, cracking. The air humidifying technology adopted in this machine can rapidly improve the relative humidity of air and prevent the skin from cracking. Strong water pump, distributed spray technology, more uniform humidiffication: a unique water pump to drive the water cycle, and the use of decentralized spray technology is the grade to in the strong water pump. In the core, so that now uniform humidification. Removable paper curtain, easy to clean; removable paper curtain, brush directly

with a soft brush clean Physical energy storage refrigeration, electricity saving, high efficiency and environmental protection: loc crystal energy storage refrigeration, loc crystal energy storage, long release time, can be used again and again for a long time, to help blow out the cocl code air. And the total outure power of 200W, 120 in general air-conditioning power consumption, this product is environmentally friendly

home appliances, fluorine free pollution. 120° degree wide-angle air supply: wide angle air supply, and set low wind, mid wind, high wind, three block wind

### speed choice



Safety Rules

1. Non full-time personnel or unauthorized repair personnel may not repair or transform the machine.

2. It is attently prohibited to operate with west hards so as to world electric shock. It is attently prohibited to operate with west hards so as to world electric shock and the prohibited so the same schoold immediately apply subject, and must be professional manufacturers or qualified full-time personnel for repair it.

5. If not use the machine for a long time, please unplug the power plug of the property of the propert

out.
21 les crystal powder in ice crystal box prohibits children from playing and avoiding careloss use.
22 When the machine is working, it is forbidden to touch or insert other objects into the air outlet so as to avoid accidents.
23 Product maintenance must be performed at the designated service point.



## Cleaning and maintenance

Function Keys Use Diagram

Cleaning and maintenance

Warm Tip: After a long period of operation, the filter and paper curtain due to dust and other dirt blockage affect the amount of air and dust effect, recommended according to the actual situation once aweek cleaning.

1. Clean the air filter Unslag the power plag, hold the air filter handle up, you can remove the air filter, trush directly with a soft brush air filter, washed with valent and order, and then back to the machine.

2. Clean the paper curtain flipsing the power plug, first remove the pair curtain filter, the machine is the proper plug. First remove the pager curtain, the paper curtain from the paper curtain remove the brush directly with a soft brush to clean the paper curtain, and finse with water, and then cleaded back to the machine.

loaded back to the machine.

3. Clean the water tank Unplug the power plug, first out of the water tank, with a sittle brush to clean the vater tank to clean the scale, and then rinse with water, and then push the water tank (fole: the bottom of the tank there is a water plug, the sewage can be released).

3. Clean the water tank (fole: the bottom of the tank there is a water plug, the sewage can be released).

3. Clean the water tank (fole: the bottom of the tank there is a water plug, power power plug, power operation. Chassis assembly any part of the control panel can not be water.






Serial No. Name	Quantity
1 Aircooler	1
2 Icebox	2
3 Manual	1
4 Wheel	4
5 Wrench	1

## Technical Parameter

QCAC-15R	
220V~50Hz	
200W	
≤76dB	
780m³/h	
950mL/h	
12.0Kg	
395x325x1000mm	
	220V-50Hz 200W \$76dB 780m³/h 950mL/h 12.0Kg

## Schematic diagram of electrical equipment



3

Installation And Use

1. Open the pockage and take out the cooling fan and place it on the horizontal floor

1. Open the pockage and take out the cooling fan and place it on the horizontal floor

1. Open the pockage and take out the cooling fan and place it on the horizontal floor

1. Open the pockage and the place in the bottom of the box.

3. Install the caster, the machine in the flat on the ground (preferably with a soft other

1. Open the place in the bottom of caracters), could be a soft or the case wheel 2 without brake caster 2, with a special wrench will not brake the caster into the formation of the control place in the place in the bottom.

4. Add water:

1. He tank not of the fuselage, then add clean tap water.

Note: O When adding water, please pay attention to the "water level display" on the tank, the water level of the fants cannot exceed "MAX"(Highest) indicates the scale.

1. Humidification, the water tank should control the total water level can not be less than "MAX" (minimum) indicating scale in the cooling effect, the less can be force or forward in the cool fan power play into the power outlet, and ensure that the contact is good, press the control paned on the "file file "button, you can run the coid fan.

CAUTION: One play the play with wet hand as a void electric shock.

When moving the machine, unplug the power out.



Function Key Use Method Tips: Before starting the pendulum must be manually open Control Panel Introduction:

# ON/OFF

DNOVEY: Press the ONIOFF button to turn on the unit. The unit starts working in mediumspeed and switches to low speed after 3 seconds when the unit is working, press the ONIOFF button spain to switch it beach to if mode. SPEED Press the SPEED button to adjust the speed. There are three positions – Low, Medium

SPEED:
Press the SPEED button to adjust the speed. There are three positions – Low, Medium or High. The corresponding indicator turns on.

4